

Pneumatic sealless steel strapping tool



Characteristics

Strapping qualities:	Uniflex and Ultraflex max. 1100 N/mm ² / 160'000 psi
Strapping dimensions:	widths 9.5 – 20.0 mm / 3/8 – 3/4"
	thicknesses 0.38 – 0.63 mm / .015 - .025"
Weights:	10.0 kg / 22.0 lbs without suspension
	10.5 kg / 23.2 lbs with suspension
Sealless joint:	Fromm MicroLock™
Average seal strength:	approx. 80 %
Strap tension:	The tool is available for four different stages of strap tension, see chart
Suspensions:	Universal suspension bracket is supplied with the tool

Advantages

- Ideal pneumatic tool to strap flat packages – high reliability eliminates down-time
- Pneumatic operation offers considerable time savings
- Air-motor for tensioning allows high and constant strap tension
- The sealless joint reduces the overall strapping costs by approx. 10% through the elimination of the seals
- With the innovative profile of the sealless punch and die the tool produces the unique MicroLock™ sealless joint preventing the seal from getting loose in case of shrinkage of the package.

Chart of types model A385

Item No.	Model	Strap widths		Thicknesses		Max. Tension		Tension speed	
		mm	inch	mm	inch	N	lbs	mm/s	inch/s
13.7010	A385/9.5/0.38-0.50/3.3	9.5	3/8"	0.38-0.50	.015-.020	3300	740	120	4.7
13.7011	A385/9.5/0.38-0.50/2.7	9.5	3/8"	0.38-0.50	.015-.020	2700	610	190	7.5
13.7020	A385/10/0.38-0.50/3.3	10		0.38-0.50	.015-.020	3300	740	120	4.7
13.7021	A385/10/0.38-0.50/2.7	10		0.38-0.50	.015-.020	2700	610	190	7.5
13.7030	A385/12.7/0.38-0.50/3.3	12.7	1/2"	0.38-0.50	.015-.020	3300	740	120	4.7
13.7031	A385/12.7/0.38-0.50/7.0	12.7	1/2"	0.38-0.50	.015-.020	7000	1570	65	2.5
13.7032	A385/12.7/0.58-0.63/3.3	12.7	1/2"	0.58-0.63	.020-.025	3300	740	120	4.7
13.7033	A385/12.7/0.58-0.63/7.0	12.7	1/2"	0.58-0.63	.020-.025	7000	1570	65	2.5
13.7034	A385/12.7/0.38-0.50/2.7	12.7	1/2"	0.38-0.50	.015-.020	2700	610	190	7.5
13.7035	A385/12.7/0.38-0.50/4.7	12.7	1/2"	0.38-0.50	.015-.020	4700	1060	100	4.0
13.7036	A385/12.7/0.58-0.63/2.7	12.7	1/2"	0.58-0.63	.020-.025	2700	610	190	7.5
13.7037	A385/12.7/0.58-0.63/4.7	12.7	1/2"	0.58-0.63	.020-.025	4700	1060	100	4.0
13.7040	A385/13/0.38-0.50/3.3	13		0.38-0.50	.015-.020	3300	740	120	4.7
13.7041	A385/13/0.38-0.50/7.0	13		0.38-0.50	.015-.020	7000	1570	65	2.5
13.7042	A385/13/0.58-0.63/3.3	13		0.58-0.63	.020-.025	3300	740	120	4.7
13.7043	A385/13/0.58-0.63/7.0	13		0.58-0.63	.020-.025	7000	1570	65	2.5
13.7044	A385/13/0.38-0.50/2.7	13		0.38-0.50	.015-.020	2700	610	190	7.5
13.7045	A385/13/0.38-0.50/4.7	13		0.38-0.50	.015-.020	4700	1060	100	4.0
13.7046	A385/13/0.58-0.63/2.7	13		0.58-0.63	.020-.025	2700	610	190	7.5
13.7047	A385/13/0.58-0.63/4.7	13		0.58-0.63	.020-.025	4700	1060	100	4.0
13.7050	A385/16/0.38-0.50/3.3	16	5/8"	0.38-0.50	.015-.020	3300	740	120	4.7
13.7051	A385/16/0.38-0.50/7.0	16	5/8"	0.38-0.50	.015-.020	7000	1570	65	2.5
13.7052	A385/16/0.58-0.63/3.3	16	5/8"	0.58-0.63	.020-.025	3300	740	120	4.7
13.7053	A385/16/0.58-0.63/7.0	16	5/8"	0.58-0.63	.020-.025	7000	1570	65	2.5
13.7054	A385/16/0.38-0.50/2.7	16	5/8"	0.38-0.50	.015-.020	2700	610	190	7.5
13.7055	A385/16/0.38-0.50/4.7	16	5/8"	0.38-0.50	.015-.020	4700	1060	100	4.0
13.7056	A385/16/0.58-0.63/2.7	16	5/8"	0.58-0.63	.020-.025	2700	610	190	7.5
13.7057	A385/16/0.58-0.63/4.7	16	5/8"	0.58-0.63	.020-.025	4700	1060	100	4.0
13.7060	A385/19/0.50-0.63/3.3	19	3/4"	0.50-0.63	.020-.025	3300	740	120	4.7
13.7061	A385/19/0.50-0.63/7.0	19	3/4"	0.50-0.63	.020-.025	7000	1570	65	2.5
13.7062	A385/19/0.50-0.63/2.7	19	3/4"	0.50-0.63	.020-.025	2700	610	190	7.5
13.7063	A385/19/0.50-0.63/4.7	19	3/4"	0.50-0.63	.020-.025	4700	1060	100	4.0
13.7070	A385/20/0.50-0.63/3.3	20		0.50-0.63	.020-.025	3300	740	120	4.7
13.7071	A385/20/0.50-0.63/7.0	20		0.50-0.63	.020-.025	7000	1570	65	2.5
13.7072	A385/20/0.50-0.63/2.7	20		0.50-0.63	.020-.025	2700	610	190	7.5
13.7073	A385/20/0.50-0.63/4.7	20		0.50-0.63	.020-.025	4700	1060	100	4.0

UNI = Uniflex regular duty strapping max. 850 N/mm² / 123'000 psi / ULT = Ultraflex high tensile strapping max. 1100 N/mm² / 160'000 psi